

Georgia Department of Public Safety

Policy Manual Exhibit

SUBJECT VEHICLE MAINTENANCE	EXHIBIT NUMBER 6.03-1
REFERENCE 6.03 – VEHICLE ASSIGNMENT	DATE REVISED 10/16/2024
	POLICY REVIEWED 10/16/2024

All DPS units, oil changes will be performed every 5,000 miles except for Camaro LT1 every 4000 miles.

Tires will be rotated at least every 10,000 miles or sooner if required.

Add other fluids as needed.

2022 – 2023 Dodge Charger Pursuit RWD

5.7L Hemi - 0W20 Full Synthetic API Starburst Trademark - do not use conventional or synthetic oil.

Engine Air Filter replace every 20,000 miles.

Cabin Air Filter replace every 20,000 miles.

Transmission Fluid and Filter not required by mfg. (sealed unit) if leak occurs, or failure, transport to a Dodge dealer for repair.

Tune Up / Replace Spark Plugs every 100,000 miles.

Coolant Flush every 100,000 miles.

Add other fluids as needed at every 5,000 miles service.

2007 – 2021 Dodge Chargers Police Package

5.7L Hemi - 5W20 Synthetic Blend - do not use conventional or pure synthetic oil.

Engine Air Filter replace every 20,000 miles.

Cabin Air Filter replace every 20,000 miles.

Power Steering Fluid checked every 30,000 miles. (2011 – 2014 RWD and All AWD Chargers)

Transmission Fluid and Filter change N/A.

Tune Up / Replace Spark Plugs every 100,000 miles.

Coolant Flush every 100,000 miles.

Add other fluids as needed at every 5,000 miles service.

2021 Dodge Challenger R/T RWD

5.7L Hemi - 0W20 Full Synthetic API Starburst Trademark - do not use conventional or synthetic oil.

Engine Air Filter replace every 20,000 miles.

Cabin Air Filter replace every 20,000 miles.

Transmission Fluid and Filter not required by mfg. (sealed unit) if leak occurs, or failure, transport to a Dodge dealer for repair.

Tune Up / Replace Spark Plugs every 100,000 miles.

Coolant Flush every 100,000 miles.
Add other fluids as needed at every 5,000 miles service.

2021 – 2023 Dodge Durango Pursuit RWD

5.7L Hemi - 0W20 Full Synthetic API Starburst Trademark - do not use conventional or synthetic blend oil.
Engine Air Filter replace every 20,000 miles.
Cabin Air Filter replace every 20,000 miles.
Transmission Fluid and Filter not required by mfg. (sealed unit) if leak occurs, or failure, transport to a Dodge dealer for repair.
Tune Up / Replace Spark Plugs every 100,000 miles.
Coolant Flush every 100,000 miles.
Add other fluids as needed at every 5,000 miles service.

2016 – 2017 Ford Explorer Police Interceptor Utility

3.5L Eco Boost - 5W30 Synthetic Blend - do not use conventional or pure synthetic oil.
Engine Air Filter replace every 20,000 miles.
Cabin Air Filter replace every 20,000 miles.
Transmission Fluid and Filter change N/A.
Tune Up / Replace Spark Plugs every 100,000 miles.
Coolant Flush every 100,000 miles.
Add other fluids as needed at every 5,000 miles service.

2022-2023 Chevrolet Camaro LT1 RWD

91 OCTANE OR HIGHER
6.2L V8 - 5W30 Full Synthetic Dexos – (EVERY 4,000 MILES)
Do not use conventional or synthetic blend oil.
Engine Air Filter replace every 20,000 miles.
Cabin Air Filter replace every 20,000 miles.
Transmission Fluid and Filter change every 50,000 miles (sealed unit) if leak occurs, or failure, transport to Chevrolet dealer for repair.
Tune Up / Replace Spark Plugs every 100,000 miles.
Coolant Flush every 100,000 miles.
Add other fluids as needed at every 4,000 miles service.

2015 – 2023 Chevrolet Tahoe Interceptor / Suburban RWD & 4WD

5.3L V8 - 0W20 Full Synthetic Dexos – do not use conventional or synthetic blend oil. [_](#)
Every 5,000 miles per GM for Law Enforcement
Engine Air Filter replace every 20,000 miles.
Cabin Air Filter replace every 20,000 miles.
Transmission Fluid and Filter change every 50,000 miles
Tune Up / Replace Spark Plugs every 100,000 miles.
Coolant Flush every 100,000 miles.
Add other fluids as needed at every 5,000 miles service.

2011 - 2014 Chevrolet Tahoe Interceptor

5.3L V8 - 5W30 Full Synthetic Dexos – do not use conventional or synthetic blend oil.
Engine Air Filter replace every 20,000 miles.
Cabin Air Filter replace every 20,000 miles.
Transmission Fluid and Filter change every 50,000 miles

Tune Up / Replace Spark Plugs every 100,000 miles.
Coolant Flush every 100,000 miles.
Add other fluids as needed at every 5,000 miles service.

2015 – 2023 Ford F250 / F350 /F450 / F550 / F650 / F-750 RWD & 4WD

Diesel 6.7L V8 -10W30 DIESEL Conventional Oil–do not use pure synthetic oil.
Diesel Exhaust Fluid (DEF) Fill every oil change or as needed.
Tire rotation interval every 10,000 miles on SRW (Single Rear Wheel) models only.
Engine Air Filter replace every 20,000 miles.
Cabin Air Filter replace every 20,000 miles.
Fuel Filters (2) replace every 15,000 miles.
Coolant Test Contamination Kit every 15,000 miles.
Transmission Fluid and Filter change every 50,000 miles.
Coolant Flush every 50,000 miles.
Add other fluids as needed at every 5,000 miles service.

Silverado PPV & SSV

5.3L V8 - 0W20 Full Synthetic Dexos – do not use conventional or synthetic blend oil. -
Every 5,000 miles per GM for Law Enforcement
Engine air filter change interval - Every 15,000 miles
Cabin air filter change interval - Every 10,000 miles
Transfer case fluid change (4x4) – Every 100,000 miles
Transmission service interval - Every 45,000 miles
Tune-up, spark plug change interval - Every 100,000 miles
Coolant flush interval – 150,000 miles
Tires 275/60 R20 Goodyear Wrangler Trail Runner AT

2024+ Mustangs

5W-30 Full synthetic – Change oil every 5,000 miles.
Engine air filter change interval - Every 5,000 miles
Cabin air filter change interval - Every 15,000 miles
Transmission service interval - 150,000 miles
Tune-up, spark plug change interval - 100,000 miles.
Coolant flush interval - 200,000 miles
Tires: Front - 255/40R19 XL Goodyear Eagle Exhilarate. Rear - 275/40R19 GDY Exhilarate

All other vehicles use Manufacturer Suggested Oil – in a Synthetic Blend or
Conventional – do not use pure synthetic oil unless it is required by manufacturer.
Engine Air Filter replace every 20,000 miles.
Cabin Air Filter replace every 20,000 miles.
Transmission Fluid and Filter change N/A.
Tune Up / Replace Spark Plugs every 100,000 miles.
Add other fluids as needed at every 5,000 miles service.

For all DPS/GSP vehicles, refer to the Owner's Manual for maintenance specifications.