

**Georgia Department of Public Safety
Policy Manual Exhibit**

SUBJECT VEHICLE MAINTENANCE	EXHIBIT NUMBER 6.03-1
REFERENCE 6.03 – VEHICLE ASSIGNMENT	DATE REVISED 10/16/2020
	POLICY REVIEWED 10/16/2020

All DPS units, oil changes will be performed every 5,000 miles. Tires will be rotated at least every 10,000 miles or sooner if required.

Vehicles have permanent type antifreeze. Do not replace or flush the system unless problems persist, refer to the Owner’s Manual for maintenance specifications.

Add other fluids as needed.

Transmissions should be serviced only if problems are experienced prior to warranty expiration. Contact the DPS Garage regarding service following warranty expiration.

2007 – 2020 Dodge Chargers Police Package

5.7L Hemi - 5W20 Synthetic Blend - do not use conventional or pure synthetic oil.
 Engine Air Filter replace every 20,000 miles.
 Cabin Air Filter replace every 20,000 miles.
 Power Steering Fluid checked every 30,000 miles. (2011 – 2014 RWD and All AWD Chargers)
 Transmission Fluid and Filter change N/A.
 Tune Up / Replace Spark Plugs every 100,000 miles.
 Add other fluids as needed at every 5,000 mile service.

2016 – 2017 Ford Police Interceptor Utility (Explorer)

3.5L Eco boost - 5W30 Synthetic Blend - do not use conventional or pure synthetic oil.
 Engine Air Filter replace every 20,000 miles.
 Cabin Air Filter replace every 20,000 miles.
 Transmission Fluid and Filter change N/A.
 Tune Up / Replace Spark Plugs every 100,000 miles.
 Add other fluids as needed at every 5,000 mile service.

2015 – 2020 Chevrolet Tahoe Interceptor / Suburban

5.3L V8 - 0W20 Full Synthetic Dexos – do not use conventional or synthetic blend oil.
 Engine Air Filter replace every 20,000 miles.
 Cabin Air Filter replace every 20,000 miles.
 Transmission Fluid and Filter change every 50,000 miles
 Tune Up / Replace Spark Plugs every 100,000 miles.
 Add other fluids as needed at every 5,000 mile service.

2011 - 2014 Chevrolet Tahoe Interceptor

5.3L V8 - 5W30 Full Synthetic Dexos – do not use conventional or synthetic blend oil.
Engine Air Filter replace every 20,000 miles.
Cabin Air Filter replace every 20,000 miles.
Transmission Fluid and Filter change every 50,000 miles
Tune Up / Replace Spark Plugs every 100,000 miles.
Add other fluids as needed at every 5,000 mile service.

2015 – 2020 Ford F250 / F350 /F450 / F550 / F650

Diesel 6.7L V8 -10W30 DIESEL Conventional Oil–do not use pure synthetic oil.
Diesel Exhaust Fluid (DEF) Fill every oil change or as needed.
Tire rotation interval every 10,000 miles on SRW (Single Rear Wheel) models only.
Engine Air Filter replace every 20,000 miles.
Cabin Air Filter replace every 20,000 miles.
Fuel Filters (2) replace every 15,000 miles.
Coolant Test Contamination Kit every 15,000 miles.
Transmission Fluid and Filter change every 50,000 miles.
Coolant Flush every 50,000 miles.
Add other fluids as needed at every 5,000 mile service.

All other vehicles use Manufacturer Suggested Oil – in a Synthetic Blend or Conventional – do not use pure synthetic oil unless it is required by manufacturer.
Engine Air Filter replace every 20,000 miles.
Cabin Air Filter replace every 20,000 miles.
Transmission Fluid and Filter change N/A.
Tune Up / Replace Spark Plugs every 100,000 miles.
Add other fluids as needed at every 5,000 mile service.

For all DPS/GSP vehicles, refer to the Owner’s Manual for maintenance specifications.