

Georgia Department of Public Safety
Policy Manual Exhibit

SUBJECT VEHICLE MAINTENANCE	EXHIBIT NUMBER 6.03-1
REFERENCE 6.03 – VEHICLE ASSIGNMENT	DATE REVISED 12/14/2006

GSP and MCCD HOV units, oil changes will be performed every 3,000 miles. Tires will be rotated at least every 9,000 miles or sooner if required.

For all other DPS units, oil changes will be performed every 5,000 miles. Tires will be rotated at least every 10,000 miles or sooner if required.

Vehicles have permanent type antifreeze. Do not replace or flush the system unless problems persist, refer to the Owner's Manual for maintenance specifications.

Add other fluids as needed.

Transmissions should be serviced only if problems are experienced prior to warranty expiration. Contact the DPS Garage regarding service following warranty expiration.

Ford Crown Victoria's:

Use 5W-20 Motor Oil for year models 2000 and later.

Use 10W-40 for models earlier than 2000.

Replace oil filter (Type FL820) at each oil change.

Replace air filter (Type FA-1032) every 6,000 miles.

Use (87 Octane) gasoline.

Speedometers are calibrated to factory size tires. If different size tires are placed on the vehicle, the speedometer must be recalibrated.

All Ford vehicles have a 3-year or 36,000 mile warranty.

For all DPS/GSP vehicles, other than Ford Crown Victoria's, refer to the Owner's Manual for maintenance specifications.